

Q3
Concl. 4

storage compartment (102) and equipment such as a radar device (104) and a camera (106) to bottom surface (58) of horizontal planar member (55) of housing (5).

[A marked-up version of the changes made to the paragraph beginning on page 7, line 21, and ending on page 8, line 2, is attached and is labeled: "Changes to the paragraph beginning on page 7, line 21, and ending on page 8, line 2: version with markings to show changes made."]

IN THE CLAIMS

Please amend claims 1 and 5, cancel claims 13-16, and add claims 17-20 as shown by the following rewritten claims.

Q4

1. (amended) A device for use as an emergency signal in a vehicle having an interior roof and a windshield, comprising;

a housing,

a plurality of light generators attached to said housing,

means for internally mounting said housing to said interior roof of said vehicle.

B1

[A marked-up version of the changes made to claim 1 is attached hereto and is labeled: "Changes made to claim 1: version with markings to show changes made."]

15

A

25

5. (amended) The device of claim 2, wherein said leading edge of said horizontal member conforms to the curvature of said windshield of said vehicle.

[A marked-up version of the changes made to claim 5 is attached hereto and is labeled:
"Changes made to claim 5: version with markings to show changes made."]

26

13
17

17. (new) A method of installing a device for use as an emergency signal in a vehicle having an interior roof and a windshield, said method comprising the steps of:

placing a device along the interior intersection of said windshield and an interior roof of a vehicle, wherein said device includes a housing and a plurality of light generators attached to said housing;

abutting said housing against the interior surface of said windshield; and

attaching said housing to said interior roof of said vehicle.

14

13

18. (new) The method as recited in claim 17, wherein said device is installed in the front of the interior of said vehicle.

15

13

19. (new) The method as recited in claim 17, wherein said device is installed in the rear of the interior of said vehicle.

16

13

20. (new) The method as recited in claim 17, wherein said device is installed in the front and the rear interior of said vehicle.

16

A